



# CC100LA120 & CC150LA110



Frame Size Type	Available Output Terminal	Continuous Current
UL Rating 50/60Hz	Motor AC Single Phase	110~120VAC
		220~240VAC
	Motor AC Three Phase	220~240VAC
		440~480VAC
		550~600VAC
		
NEMA Size		
IEC Rating	Resistive AC1	690VAC max
	Motor AC3	200~240VAC
		380~440VAC
		500~550VAC
		690VAC max
		
Coil Voltages	AC Coil	VAC 50/60Hz
Basic Dimensions	W x H x D mm	AC Coil
Accessories	Auxiliary Contacts	Standard
		Optional
		Mechanical Interlock
		Power Connector for Reversing Contactors

CC100LA120	CC150LA110
Screw Clamp Only	Screw Clamp or Lug
160A	210A
10HP	15HP
20HP	25HP
40HP	50HP
75HP	100HP
75HP	75HP
3	4
160A	210A
30kW 105A	45kW 150A
55kW 105A	75kW 150A
55kW 85A	70kW 100A
45kW 65A	55kW 60A
24, 48, 100, 110, 120, 200, 220, 230, 240, 380, 415, 440, 500, 550 VAC	24, 48, 110, 220, 300, 400, 500 VAC
3.70 (94) x 5.51 (140) x 5.35" (136mm)	4.69 (119) x 6.22 (158) x 5.16" (131mm)
2NO2NC	2NO2NC
Top Mount	
GUR02	GUR02
GUW95	