

3PSS60D75 S (Din-Rail)



3PSS60D75 S (Standard Din-Rail)

- 3-phase Solid State Relay
- Zero switching
- Rated operational current: 2 x 75 AMPS or 3 x 50 AMPS
- Rated operational voltage: 600 VAC
- Control voltage: 4-32 VDC
- 100kA Short Circuit Current Rating according to UL 508
- Line & Load accepts: **8-18 AWG**
- Integral snubber network
- Built-in varistor
- IP10 back-of-hand protection
- LED indication of control input
- Heat Sink and 24 VDC Fan



Product Description

A Solid State Relay family designed to switch various loads such as heating elements, motors and transformers. The relay is capable of switching voltages up to 600 VAC rms. The built-in varistor is for heavy industrial applications. For higher reliability and load cycle capability three semiconductor power units are bonded directly to the substrate.

General Specifications

Operational voltage range	42-660 VAC 45 to 65 Hz
Blocking voltage	1600 V _p
Over voltage category III	Pollution degree 3
Operating temperature	-30° to 80°C (-22° to 158°F)
Storage temperature	-40° to 100°C (-40° to 212°F)
Input to output isolation voltage	≥ 4000 VAC rms
Output to case isolation voltage	≥ 4000 VAC rms
Heat Sink Fan requires	70 mA @ 24 VDC

Input Specifications

All data specified at Ta=25°C

Control voltage range	4-32 VDC
Pick-up voltage	3.8 VDC
Drop-out voltage	1.2 VDC
Input current	≤ 23 mA
Response time pick-up (Power output = 50 Hz)	10 ms
Response time drop-out (Power output = 50 Hz) e	10 ms

Tested and Approved

3 Pole 50 AMPS @ 480 VAC @ -30°C to 50°C 3-Phase
 2 Pole 75 AMPS @ 480 VAC @ -30°C to 50°C 3-Phase *

51°C to 80°C derates @ 10 AMPS per decade

*For 2 Pole usage, use L1 & L3

